

ProNature HardWax Oil

You got it waxed...naturally!

Product code: PN115

Technical Data Sheet

Product Description:

ProNature HardWax Oil is a blend of plant oils and waxes that provides protection and a beautiful matt satin finish to all your interior wood surfaces. It is safe to use on everything from floors and furniture to cutting boards and toys, making it the perfect choice of woodcare. ProNature HardWax Oil is easy to apply, and maintenance is super simple. A superior top oil, water- & stain-resistant, so you can rest assured that your wood will look its best for years to come.

Ingredients:

Linseed oil, blend of vegetable oils, gum resin, beeswax, carnauba wax, silicic acid, lead-free driers, (natural and non-toxic mineral pigments in tinted product only).

TVOC (Total Volatile Organic Content) 29.10g/litre

Appearance:

ProNature HardWax Oil gives a matte, yet satin, finish.

Colour:

Natural Clear: Enhances the original wood colour.

Natural Light: Preserves the freshly sanded look on LIGHT timbers, such as Oak, Pine and Birch, avoids darkening or yellowing.

Coverage:

Approximately 20-30 m² per litre, depending on the type of wood.

For optimum durability apply 3 coats.

Application:

Watch this short video! <https://www.pronature.co.za/tips-tricks/> or scan QR Code:

Before you apply **ProNature HardWax Oil**, ensure that all surfaces are dry, clean and dust-free. If necessary, sand wood to a fine, smooth finish using min grit 100.

Can be applied as a top coat on Surfaces stained & sealed with ProNature Indoor after a minimum drying time of ProNature Indoor of 12 hours.

No cross-linking agent required.

ProNature HardWax Oil is ready to use - Do not dilute.

- ✓ Stir well!
- ✓ Apply liberally using brush, short bristle paint roller or wipe with cloth until saturated
- ✓ Remove and dry off ALL excess after **about 10 min** using a lint-free cloth e.g. **ProNature Mutton Cloth**.
- ✓ Leave to dry for a minimum of 6 hours and if necessary lightly sand the surface before applying the next coat.

NOTE: It takes about 7 days to fully cure, avoid standing water during this period.

NB: Cold weather and/or high humidity will prolong the drying process

- ✓ PACKAGING of coated items: Avoid direct contact with plastic wrapping. Use paper/cardboard/cloth as a protective layer. Items to cure for a minimum of 12 hours (e.g. overnight) prior to packaging.



Caution:

Product is ignitable! Submerge used cloths in water and store in a tightly sealed tin.

Cleaning:

Use **ProNature Plant Soap Concentrate** to clean all your brushes & rollers, for severe stains and prior to re-oiling.

General Maintenance, Care & Repair:

Use **ProNature Wood Cleaner** to clean all wooden surfaces.

Re-apply **ProNature HardWax Oil** if surface appears dry and lusterless Oil will blend in once the product has fully cured.

Storage/Shelf life:

Store in a cool, dry place. Unlimited pot life.

Disposal:

DO NOT empty this oil-based liquid residue into drains. Take to a designated municipal collection point for safe disposal

Safety:

Natural ingredients may cause allergies. Use only as directed. Keep out of reach of children.

General:

The above information given is intended as a guideline only. Since this product is used outside of our control, ProNature cannot be held liable for any loss or damage whatsoever relating to the application or surface it is applied to. We reserve the right to change specifications at any time and without prior notice.



ProNature HardWax Oil

You got it waxed...naturally!

Product code: PN115

Maintenance Sheet

Maintenance , Schedules and Recommendations for wooden surfaces:

To keep all your wooden furnishings looking beautiful, please follow the instructions and recommendations below.

Surface preparation:

Prior to applying **ProNature HardWax Oil** use **ProNature Plant Soap Concentrate** to ensure that surfaces are clean and free of grease. If necessary, sand to a smooth and even finish.

Insufficient sanding will be highlighted especially when sealing with a darker colour.

Application:

Stir well before applying.

For regular maintenance apply **ProNature HardWax Oil** using a brush or roller (choose same colour as original coating).

Wait 10 minutes and then, using a lint-free cloth, remove all remaining wax to avoid glossy spots and prolonged drying.

Leave to dry for a minimum 6 hrs.

NOTE: Only surfaces, which are subject to extreme weather conditions, should receive an additional coating after a 24hr drying period.

One coat of **ProNature HardWax Oil** is usually adequate for maintenance purposes. More coats may become necessary if maintenance had been neglected and the original coating has completely deteriorated. In this case it is recommended to re-apply ProNature as described in our Technical Data Sheet or on the product container.

Maintenance Intervals:

It is recommended to check all oiled surfaces for signs of deterioration especially within the first year after application. Maintenance should commence immediately to avoid further damage.

It is recommended to have the first scheduled maintenance take place within 6 months to a year after the first application to preserve the beauty and extend the life of your wood.

